

JOKER MACHINE GP II HIGH PERFORMANCE SPEEDWAY THROTTLE

Catalog # SW-3011, SW-3012, SW-3013, SW-3014, SW-3015



4668 Mission Blvd.
Montclair, CA 91763
909-613-0028
www.jokermachine.com
sales@jokermachine.com

Thank you for choosing Joker Machine Speedway
GP II Throttle Assembly

It is the result of several years of development and improvements learned by our continued racing efforts and desire to provide the finest racing twist throttle available.

MOUNTING INSTRUCTIONS

IMPORTANT NOTE: USE MILE LOCTITE (BLUE) ON ALL FASTENERS)

1. Slide the entire assembly into position on the handlebar and tighten the bar clamp
NOTE: DO NOT TIGHTEN EXCESSIVELY!
2. Remove the knob & window assembly from the body.
3. Install the throttle cable lug onto the throttle tube slot.
4. With the cable adapter slot facing upward, wrap the cable around the cable roller and install the throttle cable and adapter into the body.
5. Now rotate the cable adapter so the slot is closed in the body. To avoid contaminants from getting to the cable
6. No tighten the cable adapter set screw (do not over tighten).
7. Re-install the knob & window assembly.
NOTE: Do not use Loctite on or near the clear lens as it will be attacked by a chemical reaction!
8. Adjust cable play as needed and adjust the throttle stop set screw if necessary.

GP II FEATURES:

NEW! Extra lightening mill cuts on all parts

NEW! Quick cable access through the knob & window

NEW! Knurled cable adapter for easy rotation

NEW! Easy cable removal from the top of the roller without removing the roller and cable adapter from the body due to the "slotted" adapter and body

NEW! Larger cable adapter set screw that shares the same allen wrench size as the tube stop adjuster

MAINTENANCE:

AVOID HARSH CHEMICALS AND ABRASIVE SOLUTIONS WHEN CLEANING.

AVOID USE OF PRESSURE WASHERS DIRECTLY IN CONTACT WITH THE ASSEMBLY.

