

ONE PIECE DASH PANEL FOR SOFTTAILS AND DYNA WIDE GLIDE MODELS

REMOVE SEAT, UPPER DASH NUT AND LOWER DASH PANEL

INSTALL DESIGNATED BRACKETS PER YOUR APPLICATION BELOW

ASSEMBLE ALL BRACKETRY WITH MILD STRENGTH LOCTITE (BLUE).

(DO NOT TIGHTEN AT THIS POINT)

INSTALL RUBBER TRIM AROUND THE CURVED AREA OF THE DASH PAYING CLOSE


ATTENTION TO FITMENT AS YOU SLIDE IT AROUND TO EACH END

TRIM ENDS WITH A RAZOR BLADE (IF NECESSARY) TO MATCH

THE RUBBER ON THE MAIN CONSOLE AS CLOSE AS POSSIBLE

INSTALL THE DASH, BUT KEEP EVERYTHING "FINGER TIGHT" UNTIL FITMENT LOOKS RIGHT

NOW, TIGHTEN ALL HARDWARE EVENLY UNTIL YOU ESTABLISH A "SNUG" FIT ON THE TANK.



PH: (909) 613-0028
FX: (909) 613-0098
WWW.JOKERMACHINE.COM

CARE INSTRUCTIONS:

WASH WITH A MILD DETERGENT AND WARM WATER TO REMOVE ANY ROAD DEBRIS/DIRT ETC.
AND TAKE GREAT CARE TO DRY IT WITH A CLEAN TOWEL/CLOTH.

USE A ABSOLUTELY CLEAN CLOTH AND APPLY A LIGHT COAT OF A PREMIUM WAX
OFTEN TO PROTECT THE HIGH CHROME FINISH.

